



MONOFILL

Technical Datasheet

Monocouche® RXF

DESCRIPTION

An aqueous dispersion of acrylic polymers, iron oxide pigments, finely graded aggregates, controlling chemicals, which enables the infill of small defects.

It has archaeology that enables the infill of minor defects; following set it retains elasticity permitting further minor movement without the loss of adhesion properties.

It is supplied in flexible 125cc containers, which incorporate a spout that may be adjusted to provide differing thickness of discharge of material.

It is manufactured in a standard range of colours and may be blended further to Specific colouration, subject to additional cost, if required.

APPLICATION

Cut spout, in order that ribbon discharge of materials can be obtained.

Apply materials into fissure, avoiding excessive overspill onto the adjacent area.

Remove excess by rubbing with a dry clean cloth or sponge, ensuring that the texture of

The surface has not been flatted, and is a good match to the existing surface.

Allow to dry and top up any shrinkage where necessary, repeating the above technique.

Apply Mono Mend to further blend repair, if required.

COVERAGE

Depends entirely upon the size of fissure and/or defect and can only be confirmed after detailed site survey.

DRYING TIME

Two/three hours for minor defect infill, one/five hours for 6mm at 25-35C, relative humidity not exceeding 80%.

SHELF LIFE

More than three months in sealed containers. Protect from frost.

CLEANING

Clean all equipment with hot water immediately after use.

HEALTH AND SAFETY DATA

Mono Fill Infill materials are of a very low order of toxicity. However, in common with all acrylic based materials, always use in well ventilated conditions.

Remove skin contamination immediately using clean water, irrigate eye splashes with copious quantities of water and seek medical attention if irritation persists.

Keep out of reach of children and avoid run off of spillage into land drains.

Absorb spillage with absorbent and dispose of by landfill non-special waste.

ACRYLIC PRODUCT

Ensure good ventilation during application and drying.

Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.

Safety data sheet available or professional user on request.

GENERAL INFORMATION

To avoid the risk of spillage, always store and transport in a secure upright position.

DO NOT HESITATE TO CONTACT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION ON THIS PRODUCT.

